

How to lace up Elitelron suppressor wraps.

Before You Start: Here are a few easy steps on how to lace up a suppressor wrap. The example to the right uses an Elitelron BATTLEDOG 30CAL. Suppressor with a BRAVO 1 Muzzle Brake and Coyote Elitelron Suppressor Wrap. Either follow the 10 simple steps to the right or use the top, bottom, left, and right views of the Elitelron STFU 30CAL. Suppressor and Wrap at the bottom of this page as a visual guide. No matter what size, all Elitelron Suppressor Wraps are designed to be attached in exactly the same way.



Step 1: Lay the wrap flat with the suppressor exit hole pointed away, buckle side underneath to your left and straps to the right. Then simply begin to tuck together the wrap sides at the top as pictured.



Step 2: Secure the wrap by snugly pulling the straps through the buckles. Fold each strap back over and through the buckles. If the wrap matches the diameter/length of the suppressor, it will fit perfectly.



Step 3: Rotate the suppressor and wrap with the top strap up. Place the supplied cord under the wrap and bring the tips up and through the first two eyelets making sure the cord lengths are equal.



Step 4: Wrap both ends of the cord from the eyelets on the bottom side of the wrap, crossing right where the wrap edges touch. Then tightly pull each cord downward toward the next pair of eyelets.



Step 5: Rotating the wrap so the top side is up, pull one cord and then the other up and through each of the next eyelets. Then tightly pull each cord down and underneath the wrap again as in Step 3.



Step 6: Rotate the suppressor and wrap again to expose the bottom side. Now bring and cross the cords again over where the wrap edges meet. Make sure that the cords are still pulled tightly.



Step 7: Spin the suppressor and wrap 180 degrees with the weapon barrel end of the suppressor now pointing away. Bring the cords around to the bottom crossing them as before - but for the last time.



Step 8: With the top side now facing up, pull each of the cords up and through the last two eyelets. Once again, make sure that the cords are pulled taut so that the wrap can fit the suppressor tightly.



Step 9: To secure the wrap and suppressor, bring both cords up the sides ending at the middle bottom. Tie a knot. You can dab finger-nail polish on the loose cord ends and burn strap ends to prevent fraying.



Step 10: To remove a wrap without untying it, bring the ends of the cords up and around the barrel on the back of the suppressor ending at the bottom. Tie a knot. Trim off extra cord length or tuck it away.



Note: Please note that care should be taken when attaching materials for concealment purposes. Make sure that you have not blocked the view for optics or iron sights. Now you are ready to go.

Top View.



Front (Exit Hole)

Bottom View



Front (Exit Hole)

Left View



Front (Exit Hole)

Right View



Front (Exit Hole)